

Simple, balanced & good value PackPro 5.2 – the all-rounder

One side coated, wood free flexible packaging paper. With optical brightening agents. Very good runnability in printing and conversion. Good cracking resistance.

A modern paper for flexible packaging that delivers good results in all standard printing procedures. The paper displays good runnability in converting, enabling the user to achieve the high performance goals he is looking for.

PackPro 5.2 is a good option for manufacturers of branded goods that can help them present their products to the customer in an attractive and appealing way.

PackPro 5.2 - making more of your packaging

Print information

Very good results in web offset and flexographic printing, good results in gravure printing.

Varnishing

Universally varnishable.

Finishing

Laminateable using cardboard, aluminium foil and plastic film.

Special features

Conforms to 94/62/EC – heavy metal directive and BFR XXXVI, food packaging

Service Information

reel width ranging from 47 cm to 210 cm
reel diameter ranging from 65 cm to 120 cm

B&B has
ISO 9001, ISO 14001, HACCP and PEFC certification



property	unit	method					tolerance
				60	70	80	
Substance	g/m ²	ISO 536		60	70	80	+/- 4%
Caliper	µm	ISO 534, single sheet measuring		50	57	66	+/- 5%
Brightness	%	ISO 2470, R457 D65	CS	86	86	86	+/- 2
Opacity dry	%	ISO 2471		76	80	83	+/- 2
Gloss Lehmann	%	Tappi 480, 75°	CS	65	65	65	+/- 5
Smoothness Bekk	Bekk sec.	ISO 5627	RS	350	350	350	+/- 150
PPS	µm	ISO 8791-4, S, 1000 kPa		1,2	1,2	1,2	max.
Cobb 60"	g/m ²	ISO 535	CS	22	22	22	+/- 4
			RS	20	20	20	+/- 4
Tensile strength dry	N/15mm	ISO 1924-2	MD	50	54	58	- 10
			CD	29	31	33	- 7
absolute Humidity	%	ISO 287		5,5	5,5	5,5	max.

Key :
CS – Coated Side
RS – reverse Side
MD - Machine Direction
CD - Cross Direction

Testing conditions :
Standard climate ISO 187
23° Celsius, 50 % relative humidity